

shaft.

7. (Amended) A stepping motor according to claim 5, further comprising a rotary polygon mirror secured to the rotating shaft which is rotatably provided through the cylindrical bearing holder vertically mounted on the base to which the stepping motor is mounted, which rotates along with the rotating shaft, the rotary polygon mirror provided on the outer periphery of the rotor yoke with each mirror surface corresponding to a magnetic pole of the rotor of the stepping motor.

Please add new claims 11-20 as follows:

--11. A stepping motor according to any one of claim 2, wherein the arc-shaped deformation preventing groove is provided along the circumference at the side end contacting the base to which the stepping motor is mounted.--

--12. A stepping motor according to any one of claim 3, wherein the arc-shaped deformation preventing groove is provided along the circumference at the side end contacting the base to which the stepping motor is mounted.--

--13. A stepping motor according to any one of claim 2, wherein the rotor is provided opposing the stator magnetic poles on a rotor yoke secured to the rotating shaft and a notch is provided in the rotor yoke in order to leak magnetism of the rotor, further comprising a leakage flux detector for detecting leaking magnetic flux from the rotor, the leakage flux detector provided in a position opposing the notch.--

--14. A stepping motor according to any one of claim 3, wherein the rotor is provided opposing the stator magnetic poles on a rotor yoke secured to the rotating shaft and a notch is provided in the rotor yoke in order to leak magnetism of the rotor, further comprising a leakage flux detector for detecting leaking magnetic flux from the rotor, the leakage flux detector provided in a position opposing the notch.--

--15. A stepping motor according to any one of claim 4, wherein

the rotor is provided opposing the stator magnetic poles on a rotor yoke secured to the rotating shaft and a notch is provided in the rotor yoke in order to leak magnetism of the rotor, further comprising a leakage flux detector for detecting leaking magnetic flux from the rotor, the leakage flux detector provided in a position opposing the notch.--

--16. A stepping motor according to any one of claim 2, further comprising a leakage flux detector for detecting changes in magnetic poles, the leakage flux detector provided on a cylinder end surface of a cylindrical permanent magnet provided in a cylindrical shape opposing the stator magnetic poles on the rotor yoke secured to the rotating shaft.--

--17. A stepping motor according to any one of claim 3, further comprising a leakage flux detector for detecting changes in magnetic poles, the leakage flux detector provided on a cylinder end surface of a cylindrical permanent magnet provided in a cylindrical shape opposing the stator magnetic poles on the rotor yoke secured to the rotating shaft.--

--18. A stepping motor according to any one of claim 4, further comprising a leakage flux detector for detecting changes in magnetic poles, the leakage flux detector provided on a cylinder end surface of a cylindrical permanent magnet provided in a cylindrical shape opposing the stator magnetic poles on the rotor yoke secured to the rotating shaft.--

--19. A stepping motor according to any one of claim 5, further comprising a leakage flux detector for detecting changes in magnetic poles, the leakage flux detector provided on a cylinder end surface of a cylindrical permanent magnet provided in a cylindrical shape opposing the stator magnetic poles on the rotor yoke secured to the rotating shaft.--

--20. A stepping motor according to claim 6, further comprising a rotary polygon mirror secured to the rotating shaft which is rotatably provided through the cylindrical

A2  
Cemb

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100

bearing holder vertically mounted on the base to which the stepping motor is mounted, which rotates along with the rotating shaft, the rotary polygon mirror provided on the outer periphery of the rotor yoke with each mirror surface corresponding to a magnetic pole of the rotor of the stepping motor.--

REMARKS

Claims 1 - 20 are pending. By this Preliminary Amendment, claims 4-7 are amended to remove multiple dependencies. Claims 11-20 are added to compensate for the material deleted from claims 4-7. Prompt and favorable examination on the merits is respectfully requested.

The attached Appendix includes marked-up copies of each rewritten claim (37 C.F.R. 1.121(c)(1)(ii)).

Respectfully submitted,

*Thomas J. Pardini*

James A. Oliff

Registration No. 27,075

Thomas J. Pardini

Registration No. 30,411

JAO:TJP/mlb

Attached: Appendix

Date: December 14, 2001

**OLIFF & BERRIDGE, PLC**  
**P.O. Box 19928**  
**Alexandria, Virginia 22320**  
**Telephone: (703) 836-6400**

**DEPOSIT ACCOUNT USE  
 AUTHORIZATION**

Please grant any extension  
 necessary for entry;

Charge any fee due to our  
 Deposit Account No. 15-0461